

- 2 -

Application No. 09/802,834  
Amendment dated October 5, 2006  
Reply to Office Action of July 10, 2006

RECEIVED  
CENTRAL FAX CENTER

OCT 05 2006

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims

1. (Previously Presented) A post comprising an inground footing, said inground footing including a socket member that is protected against deformation while being implanted into the ground by an outer sleeve, said socket member being substantially fully inserted into said outer sleeve, said outer sleeve having trailing and leading ends, said leading end being adapted to be forcibly driven into the ground in response to a driving force applied to said trailing end, said socket member being received within said outer sleeve with said leading end of said outer sleeve extending beyond said socket member so as to define a free space extending axially below said socket member for absorbing the shock in the event that an obstacle is encountered while said footing is being driven into the ground, thereby preventing the socket member from being damaged, an elongated post segment, and a connector axially inserted into said elongated post segment and said socket member for joining said post segment and said footing together in an end-to-end relationship, said connector having a lower end portion received into said socket member in said outer sleeve and an upper end portion extending axially above the socket member into the elongated post segment.

2. (Original) A post as defined in claim 1, wherein said socket member is pressure fitted within said outer sleeve.

3. (Original) A post as defined in claim 2, wherein said socket member is fully inserted within said outer sleeve with an upper end of said socket member leveled with said trailing end of said outer sleeve.

4. (Original) A post as defined in claim 1, wherein said outer sleeve is made of a non-galvanized material, whereas said socket member is made of a galvanized material.

- 3 -

Application No. 09/802,834  
Amendment dated October 5, 2006  
Reply to Office Action of July 10, 2006

5. (Original) A post as defined in claim 1, wherein said leading end of said outer sleeve is flattened to facilitate the penetration thereof into the ground.
6. (Original) A post as defined in claim 1, wherein said outer sleeve and said socket member have respectively a square cross-section and an elliptical cross-section.
7. (Original) A post as defined in claim 1, further including at least one stabilizer removably fitted over said outer sleeve to provide lateral stability to said post.
8. (Original) A post as defined in claim 7, wherein said stabilizer includes a pair of strips having slots defined therein for allowing said strips to be inserted one into the other about said outer sleeve.
9. (Original) A post as defined in claim 8, wherein each said strip includes a first elongated segment and a second elongated segment extending at right angles from one end of said first segment, said strips being assembled together to form a pair of diverging arms on opposed sides of said sleeve.
10. (Currently amended) A footing for holding a post segment above a ground surface, comprising a socket member that is protected against deformation while being implanted into the ground by an outer sleeve, said socket member being substantially fully inserted into said outer sleeve, said outer sleeve having trailing and leading ends, wherein said trailing end is directly accessible for receiving blows thereon in order to forcibly drive said leading end into the ground, said socket member being held within said outer sleeve with said leading end of said outer sleeve extending beyond said socket member so as to define a free space extending axially below said socket member for absorbing the shock in the event that an obstacle is encountered while said footing is being driven into the ground, thereby protecting the socket member against deformation, and a connector having a lower end portion received into said socket member in said outer sleeve and an upper end extending axially outwardly from said socket member, said upper end of said connector being configured to fit within the post segment to be anchored in the ground, wherein said outer sleeve is made of non-galvanized material, whereas said socket member is made of a galvanized material.

- 4 -

Application No. 09/802,834  
Amendment dated October 5, 2006  
Reply to Office Action of July 10, 2006

11. (Original) A footing as defined in claim 10, wherein said socket member is pressure fitted within said outer sleeve.
12. (Original) A footing as defined in claim 11, wherein said socket member is fully inserted within said outer sleeve with an upper end of said socket member leveled with said trailing end of said outer sleeve.
13. (Cancelled)
14. (Original) A footing as defined in claim 10, wherein said leading end of said outer sleeve is flattened to facilitate the penetration thereof into the ground.
15. (Original) A footing as defined in claim 10, wherein said outer sleeve and said socket member have respectively a square cross-section and an elliptical cross-section.
16. (Original) A footing as defined in claim 10, further including at least one stabilizer removably fitted over said outer sleeve to provide lateral stability.
17. (Original) A footing as defined in claim 16, wherein said stabilizer includes a pair of strips having slots defined therein for allowing said strips to be inserted one into the other about said outer sleeve.
18. (Original) A post as defined in claim 17, wherein each said strip includes a first elongated segment and a second elongated segment extending at right angles from one end of said first segment, said strips being assembled together to form a pair of diverging arms on opposed sides of said sleeve.
19. (Cancelled)
20. (Cancelled)
21. (Previously presented) A post comprising a footing adapted to be driven into the ground, said footing including a socket member that is protected against deformation while being

- 5 -

Application No. 09/802,834  
Amendment dated October 5, 2006  
Reply to Office Action of July 10, 2006

implanted into the ground by an outer sleeve, said outer sleeve having trailing and leading ends, said leading end being adapted to be forcibly driven into the ground in response to a driving force applied to said trailing end, said socket member being received within said outer sleeve with said leading end of said outer sleeve extending beyond said socket member to absorb the shock and thereby protect the socket member in the event that an obstacle is encountered while said footing is being driven into the ground, an elongated post segment, and a connector axially inserted into said elongated post segment and said socket member for joining said post segment and said footing together in an end-to-end relationship, further including at least one stabilizer removably fitted over said outer sleeve to provide lateral stability to said post, wherein said stabilizer includes a pair of strips having slots defined therein for allowing said strips to be inserted one into the other about said outer sleeve.

22. (Previously presented) A post as defined in claim 21, wherein each said strip includes a first elongated segment and a second elongated segment extending at right angles from one end of said first segment, said strips being assembled together to form a pair of diverging arms on opposed sides of said sleeve.

23. (New) A footing for holding a post segment above a ground surface, comprising a socket member that is protected against deformation while being implanted into the ground by an outer sleeve, said socket member being substantially fully inserted into said outer sleeve, said outer sleeve having trailing and leading ends, wherein said trailing end is directly accessible for receiving blows thereon in order to forcibly drive said leading end into the ground, said socket member being held within said outer sleeve with said leading end of said outer sleeve extending beyond said socket member so as to define a free space extending axially below said socket member for absorbing the shock in the event that an obstacle is encountered while said footing is being driven into the ground, thereby protecting the socket member against deformation, and a connector having a lower end portion received into said socket member in said outer sleeve and an upper end extending axially outwardly from said socket member, said upper end of said connector being configured to fit within the post segment to be anchored in the ground, wherein said outer sleeve and said socket member have respectively a square cross-section and an elliptical cross-section.

RECEIVED  
CENTRAL FAX CENTER

OCT 05 2006

- 6 -

Application No. 09/802,834  
Amendment dated October 5, 2006  
Reply to Office Action of July 10, 2006

**Amendments to the Drawings:**

In response to the Draftsperson's objection under 37 CFR 1.84 or 1.52, kindly substitute the attached sheet of drawings, containing a clearer version of Figures 1 and 2, for the sheet of drawings containing Figures 1 and 2 at present on file.